

Wet Area Silicone Sealant

Description

Wet Area Silicone Sealant gives you a superior waterproof and mould resistant seal that will not shrink, crack or peel away, guaranteed for 25 years*.

Product Information

Packaging	Size	Colour
Tube	75 grams	White
Cartridge	300 grams	White
Cartridge	300 grams	Clear
Cartridge	300 grams	Black
Cartridge	300 grams	Dark Grey
Cartridge	300 grams	Ivory
Cartridge	300 grams	Light Grey
Cartridge	300 grams	Mocha
Cartridge	300 grams	Off- White

Uses

Wet Area Silicone Sealant is ideal for use on or around showers, baths, spas, plumbing fixtures and sinks. It will work on materials such as ceramic, glazed & porcelain fixtures, metal, copper & brass fittings, powder coated aluminium, aluminium, plastic laminates, rubber, glass, stainless steel and concrete.

Technical Features

- 100% Silicone Sealant
- 25 year guarantee against cracking & peeling
- Superior waterproof seal
- Mould resistant
- Neutral cure

Technical Details

Property	Typical Result
Technology	Neutral cure silicone sealant
Skin Time	5-10 minutes (weather dependent)
Sag resistance (at 10 minutes)	0 inches
Joint Movement Capability	+/- 25%

Indicative data only, not intended for preparation of specifications

How To Use

Use in a well- ventilated area. Avoid contact with skin and eyes.

1. Clean surface with turps and dry.
2. Cut nozzle at 45° angle, cut cartridge tip and fit nozzle.
3. Place in caulking gun, and apply with steady pressure, ensuring sealant is pushed into the joint.
4. Tool with a spatula dipped in detergent water within 5-10 minutes of application.
5. Clean up with turps before product skins.
6. Sealant will cure in 72 hours

Clean Up

Uncured product may be removed with mineral turpentine. Cured product can be removed with Selleys Silicone Remover or by cutting and scraping.

Handy Hints

- For neater joints, mask sides before applying sealant and remove tape before sealant skins.
- Sealant must be cleaned regularly to avoid build-up of soap scum. Use **Selleys® Rapid Mould Killer™**
- Store in a cool dry place below 30°C.
- Use within 6 months of opening

Limitations

- Not paintable. Complete painting 7 days prior to applying sealant
- Not suitable for aquariums
- Not suitable for food or drinking water contact
- Not suitable for permanent water immersion

Warnings, First Aid and Shipping Information

This information can be located on the MSDS found on the Selleys website – www.selleys.com.au